## CLAIMS

- 1. An electrophoretic dispersion liquid for an electrophoretic display apparatus, comprising:
  - a plurality of electrophoretic particles each surface of which is modified by one of a basic group and an acidic group,
- a liquid for holding said electrophoretic

  10 particles to be dispersed therein, and
  - a polydiene, having the other group, dissolved in said liquid.
- A liquid according to claim 1, wherein said
   polydiene is a graft polydiene having a grafted acidic group or a grafted basic group.
  - 3. A liquid according to Claim 1 or 2, wherein said polydiene is a polybutadiene.

20

- 4. A liquid according to Claim 1 or 2, wherein said polydiene is a polyisoprene.
- 5. A liquid according to Claim 1, wherein said polydiene has an average molecular weight of 1,000 100,000.

46 A liquid according to Claim 1, wherein said 6. polydiene has 1 - 50 acidic groups or basic groups per one molecule. A liquid according to Claim 1, wherein said 5 electrophoretic dispersion liquid contains said polydiene in an amount which is 0.01 to 3 times a weight of said electrophoretic particles. 10 A liquid according to Claim 1, wherein said 8. polydiene is dissolved in said liquid in a temperature

- range of -20 to 0 °C.
- A liquid according to Claim 1, wherein said 15 liquid is a nonpolar solvent.

## 10. A display apparatus, comprising:

20

an electrophoretic dispersion liquid which comprises a plurality of electrophoretic particles each surface of which is modified by one of a basic group and an acidic group, a liquid for holding said electrophoretic particles to be dispersed therein, and a polydiene, having the other group, dissolved in said liquid;

25 a closed cell for holding said electrophoretic dispersion liquid, and

a first electrode and a second electrode for

generating an electric field in said closed cell, said electric field being a voltage of a polarity which is alternately changed is applied between said first and second electrodes and moving said electrophoretic particles.